

multi-rail towel warmer options

	No. Tubes	Tappings Centre (mm)	Watts	Btu/h
chrome - curved				
262521 - 801mm x 450mm	17	400	319	1088
262522 - 801mm x 500mm	17	450	352	1201
262523 - 801mm x 600mm	17	550	417	1423
262524 - 1170mm x 500mm	23	450	463	1580
262525 - 1170mm x 600mm	23	550	546	1863
262526 - 1867mm x 500mm	37	450	731	2494
262527 - 1867mm x 600mm	37	550	861	2938
chrome - straight				
262514 - 801mm x 450mm	17	400	319	1088
262515 - 801mm x 500mm	17	450	348	1187
262516 - 801mm x 600mm	17	550	405	1382
262517 - 1170mm x 500mm	23	450	454	1549
262518 - 1170mm x 600mm	23	550	535	1825
262519 - 1867mm x 500mm	37	450	726	2477
262520 - 1867mm x 600mm	37	550	842	2873
white - curved				
262507 - 801mm x 450mm	17	400	367	1252
262508 - 801mm x 500mm	17	450	397	1355
262509 - 801mm x 600mm	17	550	485	1655
262510 - 1170mm x 500mm	23	450	566	1931
262511 - 1170mm x 600mm	23	550	670	2286
262512 - 1867mm x 500mm	37	450	883	3013
262513 - 1867mm x 600mm	37	550	1060	3617
white - straight				
262500 - 801mm x 450mm	17	400	367	1252
262501 - 801mm x 500mm	17	450	401	1368
262502 - 801mm x 600mm	17	550	471	1607
262503 - 1170mm x 500mm	23	450	549	1873
262504 - 1170mm x 600mm	23	550	646	2204
262505 - 1867mm x 500mm	37	450	876	2989
262506 - 1867mm x 600mm	37	550	1037	3538

dual fuel options (white - straight only)

D71600 - electric element 400W

D71601 - electric element 700W

All outputs are calculated at DT50°C inline with the European BSEN442 testing standard